

# 6000, 7500 & 8000-Watt

Along with a heavy-duty wraparound frame, this universal generator is designed with multiple voltage capabilities; perfect for the serious contractor with a demanding job site.

**Alternator:**

- Total harmonic distortion (THD) less than 5%
- 100% copper windings

**Frame:**

- Heavy-duty powder coated wraparound frame with 1-inch steel tubing
- Angled isolator design features four neoprene isolators

**Components:**

- Easy-access and protected control panel with magnetic circuit breakers and GFCI-protected receptacles
- Large low tone mufflers
- Fuel shut-off valve
- Easy-to-read fuel gauge
- Idle control
- Voltmeter/hour meter
- Heavy-duty industrial air cleaner

**Miscellaneous:**

- USDA/USFS-approved spark arrestors

**Limited Warranties:**

- 2 year alternator
- 3 year Honda and Kohler engines

**Certifications:**

- CSA Certified



GFCI 5-20R  
All Models




NEMA L14-20R  
120V/240V  
GEN-6000  
Models



NEMA L14-30R  
120V/240V  
GEN-7500 &  
8000 Models



NEMA L5-30R  
120VAC  
All Models



GEN-8000-OMKO

## 6000, 7500 & 8000-Watt – Gasoline

MODEL NO.	GEN-6000-OMHO* / GEN-6000-OMKO	GEN-7500-OMHO*	GEN-8000-OMKO*
MAX. AC OUTPUT	6000 watts	7500 watts	8000 watts
RATED AC OUTPUT	5000 watts	6500 watts	6900 watts
DISPLACEMENT/ENGINE	389cc Honda GX390 OHV / 429cc Kohler CH440 OHV	389cc Honda GX390 OHV	429cc Kohler CH440 OHV
ALTERNATOR	Brushless 120V/240V, 60Hz	Brushless 120V/240V, 60Hz	Brushless 120V/240V, 60Hz
MAX. AMPS (120V/240V)	50.0/25.0	62.5/31.25	66.7/33.3
CONT. AMPS (120V/240V)	41.7/20.8	54.2/27.1	57.5/28.75
RECEPTACLES	(2) 120V, 20A GFCI duplex (1) 120V/240V, 20A twist lock (1) 120V, 30A twist lock	(2) 120V, 20A GFCI duplex (1) 120V, 30A twist lock (1) 120V/240V, 30A twist lock	(2) 120V, 20A GFCI duplex (1) 120V, 30A twist lock (1) 120V/240V, 30A twist lock
CIRCUIT BREAKERS	(1) Main circuit breaker (2) 20A toggle circuit breakers, single pole (1) 20A toggle circuit breaker, double pole (1) 30A toggle circuit breaker, single pole	(2) 20A toggle circuit breakers, single pole (1) 30A toggle circuit breaker, single pole (1) 30A toggle circuit breaker, double pole	(2) 20A toggle circuit breakers, single pole (1) 30A toggle circuit breaker, single pole (1) 30A toggle circuit breaker, double pole
RATED SPEED	3600 RPM	3600 RPM	3600 RPM
DECIBEL RATING	77.1	80.0	78.2
FUEL CAPACITY	7.3 gallons	7.3 gallons	7.3 gallons
RUN TIME (AT FULL LOAD)	8.0 hours	6.9 hours	6.9 hours
DIMENSIONS (LxWxH)	29x24.4x22.5in.	29x24.4x22.5in.	29x24.4x22.5in.
SHIP WT.	232 lb.	255 lb.	255 lb.
NET WT.	210 lb.	233 lb.	233 lb.

Noise level tested at seven meters (75% load). Rating represents minimum noise level rating.  
\*Available with electric start - battery included.

**Accessories:**

PART NUMBER	DESCRIPTION	FITS MODELS	PART NUMBER	DESCRIPTION	FITS MODELS
32-0915	RV generator adapter	All models	AW-5740-0010	Wheel kit with flat-free tires	All models
AW-5090-0004	Lifting hook	All models	AW-6000-1002	Equipment cover	All models